



Technical Specifications



100K Linear Soft Sun

Head

| | |
|-------------------|--------------------------------------|
| Wattage | 100,000 |
| Lamp Type | ESL |
| Color Temperature | 5400°K |
| CRI | 96 |
| Dimensions | 118" x 33" x 22" (295 x 825 x 55 cm) |
| Weight | 320 lbs. (145 Kg) |

Power Supply – Flicker Free (DC)

The 25K, 50K and 100K SoftSun lights utilize the same DC Flicker-Free power supply.

| | |
|-------------------|---|
| Input Power | 208-240 VAC for 25K & 50K, and 480 VAC for 100K or 380VAC for 25K, 50K or 100K |
| 50/60HZ | Three Phase |
| Power Consumption | 125 amps for 25K, 225 amps/50K, 265 Amps/100K |
| Dimensions | 25" x 30" x 45" (62 x 75 x 113 cm) |
| Weight | 440 lbs. (200 Kg) |

Photometrics in Foot Candles

Beam Angle (Spot) 16° Vertical 100° Horizontal

| | | | | | | | |
|-----|------|-------|-------|-------|-------|-------|-------|
| 5ft | 10ft | 25ft | 50ft | 75ft | 100ft | 150ft | 200ft |
| N/A | N/A | 8,330 | 2,400 | 1,111 | 630 | 278 | 151 |

Beam Angle (Flood) 35° Vertical 100° Horizontal

| | | | | | | | |
|-----|------|------|------|------|-------|-------|-------|
| 5ft | 10ft | 25ft | 50ft | 75ft | 100ft | 150ft | 200ft |
| N/A | N/A | 3830 | 1147 | 526 | 297 | 131 | 62 |

LIGHTNING STRIKES!
800-321-3644

6601 Santa Monica Blvd., Hollywood, CA 90038 Tel: 323 461-6361 / Fax: 323 461-3067