



Technical Specifications



25K Linear Soft Sun

Head

Wattage	25,000
Lamp Type	ESL
Color Temperature	5400°K
CRI	96
Dimensions	65" x 28" x 24" (163 x 70 x 60 cm)
Weight	140lbs (64 Kg)

Power Supply – Flicker Free (DC)

The 25K, 50K and 100K SoftSun lights utilize the same DC Flicker-Free power supply.

Input Power	208-240 VAC for 25K & 50K, and 480 VAC for 100K or 380VAC for 25K, 50K or 100K
50/60HZ	Three Phase
Power Consumption	125 amps for 25K, 225 amps/50K, 265 Amps/100K
Dimensions	25" x 30" x 45" (62 x 75 x 113 cm)
Weight	440 lbs. (200 Kg)

Photometrics in Foot Candles

Beam Angle (Spot) 13° Vertical 100° Horizontal

5ft	10ft	25ft	50ft	75ft	100ft	150ft	200ft
N/A	N/A	1,800	450	200	109	N/A	N/A

Beam Angle (Flood) 36° Vertical 100° Horizontal

5ft	10ft	25ft	50ft	75ft	100ft	150ft	200ft
N/A	N/A	590	150	66	44	N/A	N/A

LIGHTNING STRIKES!
800-321-3644