



Technical Specifications



50K Linear Soft Sun

Head

| | |
|-------------------|------------------------------------|
| Wattage | 50,000 |
| Lamp Type | ESL |
| Color Temperature | 5400°K |
| CRI | 96 |
| Dimensions | 82" x 33" x 23" (205 x 83 x 58 cm) |
| Weight | 210 lbs. (95 Kg) |

Power Supply – Flicker Free (DC)

The 25K, 50K and 100K SoftSun lights utilize the same DC Flicker-Free power supply.

| | |
|-------------------|---|
| Input Power | 208-240 VAC for 25K & 50K, and 480 VAC for 100K or 380VAC for 25K, 50K or 100K |
| 50/60HZ | Three Phase |
| Power Consumption | 125 amps for 25K, 225 amps/50K, 265 Amps/100K |
| Dimensions | 25" x 30" x 45" (62 x 75 x 113 cm) |
| Weight | 440 lbs. (200 Kg) |

Photometrics in Foot Candles

Beam Angle (Spot) 11° Vertical 100° Horizontal

| | | | | | | | |
|-----|------|-------|------|------|-------|-------|-------|
| 5ft | 10ft | 25ft | 50ft | 75ft | 100ft | 150ft | 200ft |
| N/A | N/A | 3,800 | 1040 | 472 | 267 | 116 | 68 |

Beam Angle (Flood) 35° Vertical 100° Horizontal

| | | | | | | | |
|-----|------|-------|------|------|-------|-------|-------|
| 5ft | 10ft | 25ft | 50ft | 75ft | 100ft | 150ft | 200ft |
| N/A | N/A | 1,680 | 420 | 186 | 105 | 46 | 25 |

LIGHTNING STRIKES!
800-321-3644